

## NAME

RCS – [incr Tcl] Revision Control System interface.

## SYNOPSIS

```
package require RCS
RCS objName [CLASS OPTIONS]
objName method [METHOD OPTIONS]
```

## CLASS OPTIONS

<i>-dir</i>	Current directory.
<i>-refresh</i>	Background refresh rate.
<i>-editor</i>	Editor.
<i>-manbrowser</i>	Man page browser.
<i>-rev</i>	Symbolic revision name (default {}).

## PUBLIC METHODS

### **version**

Return the version number. The RCS version number is returned.

### **help**

Return the help text. Help intro is returned.

### **getRevision** *newRev* *browseMode*

Allow user to select a revision or enter a new one. The user will be allowed to select one or more old revisions (depending on *browseMode*) or enter a new revision (depending on *newRev*). The selected revision(s) will be stored in *revSelect* and the return code will be stored in *revReturn*. Return 0 if ok or 1 if not (cancelled, etc).

## METHOD OPTIONS

<i>newRev</i>	Allow user to enter a revision (boolean, optional, default false).
<i>browseMode</i>	Mode to set listbox into (optional, default browse).

### **selectFile** *fileName*

Allow a user to select a file in the current directory. The *fileName* will be set in the *hlist*. Nothing will be returned. Errors will propagate.

## METHOD OPTIONS

<i>fileName</i>	Name of the file to select.
-----------------	-----------------------------

## AUTHOR

Written by Tom Allard <tallard@frb.gov>